



KEY

- Cone
- Sign

DETAIL B

Single-Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.  
 Single-Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.  
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:  
 1) During darkness, warning lights to BS EN 12362:2008 should be provided in accordance with Table A1.3 (Appendix 1).  
 2) 45° tapers have 1.5m spacing, no relaxations.  
 3) On motorways and dual carriageways with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1

Single-Dual carriageway 40mph or less - 450mm traffic cones.  
 Single-Dual carriageway 50mph or more - 750mm traffic cones.

Notes:  
 1) During darkness, warning lights to BS EN 12362:2008 should be provided in accordance with Table A1.3 (Appendix 1).  
 2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Rev	Description	By	Chkd	Date
A	Removed no right turn on Terminal Road.	JB	TW	18/02/20

Revisions

Client



Project  
 Damson Parkway  
 Solihull  
 Grid ref: 416881, 282931

Title  
 Closure  
 Detail  
 Phase 3



Charter House 848 Tyburn Road, Birmingham, B24 9NT

Design: TW	Drawn: DM	Chkd: TW
Date: 06/01/20	Date: 06/01/20	Date: 06/01/20
Scale: NTS @ A3	Status: PROPOSED	
Drawing No	15259.009.1	Rev: A