



KEY

Cone

Sign

Work area

Closed area

Traffic light head

1

Traffic light phase

Vehicle diversion route

Pedestrian diversion route

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.  
Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.  
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2) 45 degree tapers have 1.5m spacing and no relaxations.  
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C2

Single carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Lane 2 Closure or Shuttle Lane

Various  
3.5m Min  
Various  
Various

Min width of sideways safety zone (S)

0.5 m

Min length of longways clearance (L)

0.5 m

Speed of the road

30

Rev

Description

By

Chk

Date

Revisions

Client:

telent

talent with technology

Project:

Princes Way,  
Solihull, B91 3LT  
Grid Ref: (x)414778; (y)279539

Title:

Temporary Three Way  
Traffic Lights (2 Phase),  
Pedestrian crossings, Road  
narrows, Partial road closure &  
diversion

DOOCEY

Traffic Management

Design:

AW

Drawn:

AW

Chkd:

PO

Date:

10/01/2025

Date:

10/01/2025

Date:

10/01/2025

Scale:

A3 - NTS

Status:

Proposed

Drawing No

DTM24519 - 001

Rev:

-