

Desktop survey undertaken from google street view with imagery dated: April 2022

All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice).

Pedestrian management to be installed and managed to suit site conditions in accordance with current legislation & codes of practice by the contractor unless otherwise stated.

All signage and road markings shall conform with the Traffic Signs

Sign locations are indicative only, exact location to be determined on site.

Suitably qualified operative to assess site to ensure the installation complies with all current legislation. Any issues and/or changes from the original design should be immediately reported to the relevant contracts

This design is only valid for 12months from date of production and should be re-evaluated if installation is to take place after this period.

SIGN SCHEDULE	
Qty: 1 Ref: 13-9-RCAO Road Closed Access Only	Diversion
Qty: 2 Ref. 13-9-RCAO Road Closed Access Only	ROAD AHEAD CLOSED
Qty: 1 Ref: 13-9-RCAO Road Closed Access Only	ROAD AHEAD CLOSED
Qty: 2 Ref: 2702 End of temporary diversion route	Diversion ENDS
Qty- 2 Ref: 2702 Start of temporary diversion route	Diversion
Qty: 2 Ref: 2702 Start of temporary diversion route	Diversion -
Qty: 1 Ref: 2702 Start of temporary diversion route	Diversion
Qty: 6 Ref: 2704 Direction of temporary diversion route	Diverte traffic
Qty: 2 Ref: 2704 Direction of temporary diversion route	Diverted traffic
Qty: 2 Ref: 2706 Roundabout ahead leading to temporary diversion route	Diverted traffic
Qty: 1 Ref. 2706 Roundabout ahead leading to temporary diversion route	Divertind traffic
Qty: 2 Ref: 2706 Roundabout ahead leading to temporary diversion route	Diverted traffic
Qty: 2 Ref: 2706 Roundabout ahead leading to temporary diversion route	Diverted traffic
Qty: 1 Ref: 2706 Roundabout ahead leading to temporary diversion route	Piverted traffic
Qty: 1 Ref: 2706 Roundabout ahead leading to temporary diversion route	Diverted traffic
Qty: 1 Ref: 3 leg rbout 3 leg rbout	Direction of the state of the s
Qty: 1 Ref: 3 leg rbout 3 leg rbout	Diverted Treffic
Qty: 2 Ref. 573 Direction to hazard left	<b>—</b>
Qty: 4 Ref: 7001 Road works ahead	
Qhy: 6 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Ahead Closed	ROAD AHEAD CLOSED
Qty: 3 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Closed	ROAD CLOSED

1/2			$\overline{}$
Key:			
$\boxtimes\!\!\!\boxtimes$	Works Area		Temporary Traffic Signal
	Closure	8	Stop & Go Board
	Vehicular Diversion Route		Temporary Ped Signal
<b>-</b> ⊁-	Ped Diversion Route	•	Existing Bus Stop
•	Cone	•	Temporary Sign
•	Datum Point	+-+	Pedestrian Barrier

Min width of sideways safety zone (S)	
Min length of longways clearance (L)	

Cita informatio							$\overline{}$
Site information	on:  HASLUCKS GREEN ROAD, SHIRLEY, SOLIHULL						
Local Authority	SOLIHULL						
USRN	35005172						
Road Type	Single lane carriageway Road Width N/A						
Works Location	X:410668 Y:278348						
Surveyed	X	Bus Stop(s)	~	_	Parked Ve	hicles	✓
Perm Signals	X	Controlled Crossing	)	(	Cycle Land	es	X

rks Location	X:410668			Y:278348		
veyed	X	Bus Stop(s)	~		Parked Vehicles	<b>√</b>
m Signals	X	Controlled Crossing	)	(	Cycle Lanes	X
						_
hapter 8 details:						
etail B B						
ngle/Dual carriageway 40mph or less-450mm traffic cones. ngle/Dual carriageway 50mph or more-750mm traffic cones. lal carriageway national speed limit - 750mm traffic cones. axation 3m.						
otes:						

be provided in accordance with Table A1.3 (Appendix 1).

2) 45° tapers have 1.2m spacing, no relaxations.

3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes. Detail C1 C1

Single/Dual carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Single carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.

During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.



total traffic & event management solutions
Old Arden Brickworks | Bickenhill | Solihull |West Midlands | B92 0DY
t +44 (0)800 819 9001 | f +44 (0)1675 442507 info@traffixuk.com | www.traffixuk.com

Traffic Management Drawing title: Proposed Road Closure Haslucks Green Road

B90 2NH		
Date:	Scale:	Paper:
11/06/2025	NTS	A2
Drawn:	Checked:	Approved:
BN	MO	MB
Project Number: TFX MBA981	Drawing Number: 006	Revision:

This drawing is copyright & the property of Traffix & must not be copied in whole or in part without their written permission. Copyright is reserved. © This drawing must not be scaled.

The Contractor is to report all discrepancies & errors to the Contract Manage prior to works commencing.