

Desktop survey undertaken from google street view with imagery

All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice).

Pedestrian management to be installed and managed to suit site conditions in accordance with current legislation & codes of practice by the contractor unless otherwise stated.

All signage and road markings shall conform with the Traffic Signs

Sign locations are indicative only, exact location to be determined on site.

Suitably qualified operative to assess site to ensure the installation complies with all current legislation. Any issues and/or changes from the original design should be immediately reported to the relevant contracts

This design is only valid for 12months from date of production and should be re-evaluated if installation is to take place after this period.

| SIGN SCHEDULE | T |
|--|-------------------------|
| Qty: 2 Ref: 2702 End of temporary diversion route | Diversion ENDS |
| Qty: 1 Ref: 2702 Start of temporary diversion route | Diversion |
| Qty: 1 Ref: 2702 Start of temporary diversion route | Diversion |
| Qty: 1 Ref: 2702 Start of temporary diversion route | Diversion |
| Qty: 2 Ref: 2703 Direction of temporary diversion route from junction ahead | ← Divertrafi |
| Qty: 2 Ref: 2703 Direction of temporary diversion route from junction ahead | Diverted traffic |
| Qty: 4 Ref: 2704 Direction of temporary diversion route | Divert traff |
| Qty; 2 Ref: 2704 Direction of temporary diversion route | Diverted traffic |
| Qty: 1 Ref: 2706 Roundabout ahead leading to temporary diversion route | Divert |
| Qty: 1 Ref: 2706 Roundabout ahead leading to temporary diversion route | Diverted traffic |
| Qty; 3 Ref: 573 Direction to hazard left | — |
| Qty: 2 Ref: 573 Direction to hazard right | |
| Qty. 9 Ref: 7001 Road works ahead | |
| Oty. 6 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Closed | ROAD CLOSED |
| Qty: 5 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Ahead Closed | ROAD AHEAD CLOSED |

| Key: | | | |
|------|---------------------------|-----|--------------------------|
| | Works Area | | Temporary Traffic Signal |
| | Closure | 8 | Stop & Go Board |
| | Vehicular Diversion Route | | Temporary Ped Signal |
| -*- | Ped Diversion Route | • | Existing Bus Stop |
| • | Cone | • | Temporary Sign |
| • | Datum Point | 1-1 | Pedestrian Barrier |
| | | | |

| Safety information: | _ |
|---------------------------------------|---|
| Min width of sideways safety zone (S) | |
| Min length of longways clearance (L) | |
| | |
| | |
| | |

| Site information: | | | | | | |
|-------------------|------------------------------------|------------------------|-------------------|-----------------|--|--|
| NSG | SANDY HILL ROAD, SHIRLEY, SOLIHULL | | | | | |
| Local Authority | SOLIHULL | | | | | |
| USRN | 35005332 | | | | | |
| Road Type | Single lane carriageway | | Road Width Varies | | | |
| Works Location | X:411234 | | Y:279781 | | | |
| Surveyed | X | Bus Stop(s) | | Parked Vehicles | | |
| Perm Signals | | Controlled Crossing | | Cycle Lanes | | |


| , | Crossing | | Cycle Lanes | | |
|--|----------|-------------------|-------------|--|--|
| | | | | | |
| Chapter 8 details: | | | | | |
| Detail B B | | 1, | .5m | | |
| Single/Dual carriageway 40mph or less-450mm traffic cones. Single/Dual carriageway 50mph or more-750mm traffic cones. Dual carriageway national speed limit - 750mm traffic cones. relaxation 3m. | | | | | |
| Notes: 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1). 2) 45° tapers have 1.2m spacing, no relaxations. 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes. Detail C1 1 | | | | | |

Single/Dual carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.

1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Single carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.

During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.





total traffic & event management solutions Old Arden Brickworks | Bickenhill | Solihull | West Midlands | B92 0DY t +44 (0)800 819 9001 | f +44 (0)1675 442507 info@traffixuk.com | www.traffixuk.com

| Traffic Management | | | | |
|--|---------------------|-----------------|--|--|
| Drawing title: Proposed Road Sandy Hill Roa Solihull B90 2EU | | | | |
| Date: 16/09/2025 | Scale: NTS | Paper: A2 | | |
| Drawn: BN | Checked: CM | Approved: MT | | |
| Project Number: TFX MT3263 | Drawing Number: 001 | Revision: | | |

This drawing is copyright & the property of Traffix & must not be copied in whole or in part without their written permission. Copyright is reserved. © This drawing must not be scaled.

The Contractor is to report all discrepancies & errors to the Contract Manager prior to works commencing.