



Desktop survey undertaken from google street view with imagery dated: July 2024

All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice).

Pedestrian management to be installed and managed to suit site conditions in accordance with current legislation & codes of practice by the contractor unless otherwise stated.

All signage and road markings shall conform with the Traffic Signs Regulations and General Directions (TSRGD).

Sign locations are indicative only, exact location to be determined on site.

Suitably qualified operative to assess site to ensure the installation complies with all current legislation. Any issues and/or changes from the original design should be immediately reported to the relevant contracts manager/designer.

This design is only valid for 12months from date of production and should be re-evaluated if installation is to take place after this period.

SIGN SCHEDULE	
Qty 4 Ref: 13.9 Schedule 13.9: Temporary Information	
Qty 1 Ref: 13.9 Road Ahead Closed with Right Arrow Variant	
Qty 1 Ref: 13.9 Schedule 13.9: Temporary Information	
Qty 4 Ref: 2702 Start of temporary diversion route	
Qty 2 Ref: 2702 Start of temporary diversion route	
Qty 2 Ref: 2702 End of temporary diversion route	
Qty 2 Ref: 2702 Start of temporary diversion route	
Qty 1 Ref: 2703 Direction of temporary diversion route u-turn at roundabout ahead	
Qty 4 Ref: 2704 Direction of temporary diversion route	
Qty 1 Ref: 2706 Roundabout ahead leading to temporary diversion route	
Qty 1 Ref: 2706 Roundabout ahead leading to temporary diversion route	
Qty 1 Ref: 573 Direction to hazard left	
Qty 1 Ref: 573 Direction to hazard right	
Qty 4 Ref: 7001 Road works ahead	
Qty 8 Ref: 7010-FP-13.9 Nature of temporary hazard ahead - Road Ahead Closed	
Qty 3 Ref: 7010-FP-13.9 Nature of temporary hazard ahead - Road Closed	

- AWS signage installed at least 2 weeks prior to works commencing. Dates & durations to be confirmed.
- Parked vehicles/parking bays are present and could interfere with the works. No parking cones are to be installed prior to works commencing with appropriate signage if required.
- Bus stop(s) are present/in close proximity to the works. Bus stops(s) are to be suspended and the appropriate signage installed in suitable locations to be agreed on site.

Key:	
	Works Area
	Closure
	Vehicular Diversion Route
	Ped Diversion Route
	Cone
	Datum Point
	Temporary Traffic Signal
	Stop & Go Board
	Temporary Ped Signal
	Existing Bus Stop
	Temporary Sign
	Pedestrian Barrier

Safety information:	
Min width of sideways safety zone (S)	0.5m
Min length of longways clearance (L)	0.5m
Streetsbrook Road	

Site information:	
NSG	Streetsbrook Road, Solihull
Local Authority	Warwickshire
USRN	35010036
Road Type	Single lane carriageway
Works Location	X:412204 Y:280360
Surveyed	<input checked="" type="checkbox"/> Bus Stop(s) <input checked="" type="checkbox"/> Parked Vehicles <input checked="" type="checkbox"/>
Perm Signals	<input checked="" type="checkbox"/> Controlled Crossing <input checked="" type="checkbox"/> Cycle Lanes <input checked="" type="checkbox"/>

Chapter 8 details:

Detail B (B)

 Single/Dual carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones. Dual carriageway national speed limit - 750mm traffic cones. relaxation 3m.

Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) 45° tapers have 1.2m spacing, no relaxations.
 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

Detail C1 (C1)

 Single/Dual carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

Detail C2 (C2)

 Single carriageway 40mph or less - 450mm traffic cones. Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Rev	Date	Comments	By	Chk

Balfour Beatty
 Living Places
 Working in Partnership with
traffix

total traffic & event management solutions
 Old Arden Brickworks | Bickenhill | Solihull | West Midlands | B92 0DY
 t +44 (0)800 819 9001 | f +44 (0)1675 442507
 info@traffixuk.com | www.traffixuk.com

Project title:		
Traffic Management		
Drawing title:		
Proposed Diversion Route Streetsbrook Road Solihull B90 3PE		
Date:	Scale:	Paper:
24/03/2026	NTS	A2
Drawn:	Checked:	Approved:
LO	MO	MT
Project Number:	Drawing Number:	Revision:
TFX MT3408	001	-

This drawing is copyright & the property of Traffix & must not be copied in whole or in part without their written permission. Copyright is reserved. © This drawing must not be scaled.
 The Contractor is to report all discrepancies & errors to the Contract Manager prior to works commencing.